

| Product   | Name  | Ratio                                 | Delivery Form |
|---|---|---------------------------------------|---------------|
| <b>A</b>  |   |                                       |               |
| AlMoV   | <b>Aluminum Molybdenum Vanadium</b>                           | 18:41:41 wt%; other ratios on request | Granules      |
| AlMoVCrTi                                       | <b>Aluminum Molybdenum Vanadium Chromium Titanium</b>         | 25:25:25:15:10 wt%                    | Powder        |
| AlNbSiTi  | <b>Aluminum Niobium Silicon Titanium</b>                      | 50:25:5:20 wt%                        | Powder        |
| AlSnZrMo  | <b>Aluminum Tin Zirconium Molybdenum</b>                      | 28:12:24:36 wt%                       | Granules      |
| AlSnZrMoCr                                      | <b>Aluminum Tin Zirconium Molybdenum Chromium</b>             | 30:12:12:23:23 wt%                    | Granules      |
| <b>C</b>  |   |                                       |               |
| Cr Metal  | <b>Chromium Metal</b>   | > 99 %                                | Lumps         |
| Cr Metal Hearts                                 | <b>Chromium Metal Hearts</b>                                  | > 99.3 %                              | Granules      |
| CrAl  | <b>Chromium Aluminum (for pack aluminizing)</b>               | 50:50, 70:30 wt%                      | Granules      |
| <b>F</b>  |   |                                       |               |
| FeNb  | <b>Ferro Niobium high purity</b>                              | 40:60 wt% Nb                          | Powder        |
| FeNb  | <b>Ferro Niobium high purity</b>                              | 40:60 wt% Nb                          | Lumps         |
| FeV   | <b>Ferro Vanadium</b>   | 60, 80 wt% V                          | Powder        |
| <b>H</b>  |   |                                       |               |
| Hydrogen storage alloy Hydralloy <sup>®</sup> C | <b>Hydrogen storage alloy Hydralloy<sup>®</sup> C</b>         | on request                            | Granules      |
| <b>M</b>  |   |                                       |               |
| MoAl  | <b>Molybdenum Aluminum (vacuum grade)</b>                     | 50-55 wt%                             | Powder        |
| MoAl  | <b>Molybdenum Aluminum produced by aluminothermic process</b> | 65:35 wt%                             | Powder        |
| MoAlTi  | <b>Molybdenum Aluminum Titanium (vacuum grade)</b>            | 55:40:5 wt%                           | Powder        |
| <b>N</b>  |   |                                       |               |
| NbAl  | <b>Niobium Aluminum vacuum grade</b>                          | 60:40 wt%                             | Powder        |
| NbCr  | <b>Niobium Chromium</b>                                       | 80:20 wt%                             | Powder        |
| NiNb hp   | <b>Nickel Niobium high purity</b>                             | 40:60 wt%                             | Powder        |
| NiNb hp   | <b>Nickel Niobium high purity</b>                             | 40:60 wt%                             | Lumps         |

No. 12 | June 2023



# \_ALLOYS

## Product List A-Z

| Product  | Name  | Ratio                   | Delivery Form |
|----------|---|-------------------------|---------------|
| <b>S</b> |   |                         |               |
| SiTi     | <b>Silicon Titanium</b>                       | 60:40 wt%               | Powder        |
| <b>V</b> |   |                         |               |
| VAI      | <b>Vanadium Aluminum</b>                      | 50:50, 65:35, 85:15 wt% | Granules      |
| VAI      | <b>Vanadium Aluminum</b>                      | 65:35 wt%               | Lumps         |
| VAI      | <b>Vanadium Aluminum fully inspected</b>      | 50:50, 65:35 wt%        | Granules      |
| VAIC     | <b>Vanadium Aluminum Carbon</b>               | 65:34:1 wt%             | Granules      |
| VAIFe    | <b>Vanadium Aluminum Iron</b>                 | 69:19:12 wt%            | Granules      |
| VAIFe    | <b>Vanadium Aluminum Iron fully inspected</b> | 69:19:12 wt%            | Granules      |

No. 12 | June 2023

Additional materials, ratios, and services are available. Please contact us directly for further information.

#### AMG TITANIUM ALLOYS & COATINGS

GfE Metalle und Materialien GmbH  
Höfener Str. 45, 90431 Nürnberg  
Germany  
www.gfe.com

#### Contact: Peter Kottusch

Director of International Sales  
Phone: +49 911 9315 299  
Fax: +49 911 9315 1299  
E-mail: peter.kottusch@gfe.com

