Ammonium Polyvanadate

GfE Article no. 2008 629

Formula
$(NH_4)_2V_6O_{16}$

Grade
Yellow dried

Appearance
Orange powder

Application

- CATALYST INDUSTRY
  Used for sulfuric acid, adipic acid.
- CERAMIC INDUSTRY
  Used for colorizing, glazing.
- ENAMELLING INDUSTRY
  Used for low melting enamel frits, e.g. for coating of aluminum.
- FERTILIZER (AMMONIA, UREA) HYDROGEN (H_2O_2, METHANOL)
  Used for corrosion inhibition in carbon dioxide scrubbers (gas sweetening) of types Benfield, Ventrocoke, Catacarb, Carbosolvan, Carsol and Girbotol.

Packaging
Steel drums 25 - 180 kg
Other packing on request.

ADR/RID, IMDG, ICAO/IATA class 6.1

CAS no.	12207-63-5
UN no.	2861

Chemical Analysis in wt%

V_2O_5	≥87.5
V	≥49
Na	≤0.05
K	≤0.015
Fe	≤0.03

Other elements on request.

Physical Properties

Size:	less than 3 mm

No. 8 | Juli 2026

AMG TITANIUM
GfE Metalle und Materialien GmbH
Höfener Str. 45, 90431 Nürnberg
Germany
www.amg-titanium-de.com

Contact: Alicja Dulat
Phone: +49 (0)911 9315-263
E-mail: alicja.dulat@amg-titanium-de.com